

Модельный ряд Vortice Punto - 3 размера: Ø 100, 120 и 150 мм

Модель	Код	Мощность, Вт	Потреб. ток, А	Расход, м3/ч	Напор, мм вод.ст.	Степень защиты IP	Кол-во в упак. Коробке	Лр на расст. 3м. дБа
M 100/4"	11201	18	0,1	90	3	X4	12	38
M 100/4" P	11641	18	0,1	90	3	X4	4	
M 100/4" T	11211	18	0,1	90	3	X4	6	
M 100/4" A	11221	18	0,1	90	3	X4	6	
M 100/4" AP	11646	18	0,1	90	3	X4	4	
M 100/4" AT	11231	18	0,1	90	3	X4	4	
M 100/4" LL	11202	18	0,1	90	3	X4	6	
M 100/4" T LL	11212	18	0,1	90	3	X4	6	
M 100/4" PIR LL	11682	18	0,1	90	3	X4	4	
M 100/4" T HCS LL	11602	18	0,1	90	3	X4	4	
M 100/4" MHC LL	11627	18	0,1	90	3	X4	4	
M 100/4" A LL	11222	18	0,1	90	3	X4	6	
M 100/4" AT LL	11232	18	0,1	90	3	X4	4	
M 100/4" A PIR LL	11684	18	0,1	90	3	X4	4	
M 100/4" T HCS	11601	18	0,1	90	3	X4	4	
M 100/4" AT HCS LL	11612	18	0,1	90	3	X4	4	
M 100/4" A MHC LL	11637	18	0,1	90	3	X4	4	
M 120/5"	11301	20	0,12	175	4,5	X4	4	40,5
M 120/5" P	11741	20	0,12	175	4,5	X4	4	
M 120/5" T	11311	20	0,12	175	4,5	X4	4	
M 120/5" A	11321	20	0,12	175	4,5	X4	4	
M 120/5" AP	11746	20	0,12	175	4,5	X4	4	
M 120/5" AT	11331	20	0,12	175	4,5	X4	4	
M 120/5" LL	11302	20	0,12	175	4,5	X4	4	
M 120/5" T LL	11312	20	0,12	175	4,5	X4	4	
M 120/5" PIR LL	11782	20	0,12	175	4,5	X4	4	
M 120/5" A LL	11322	20	0,12	175	4,5	X4	4	
M 120/5" AT LL	11332	20	0,12	175	4,5	X4	4	
M 120/5" A PIR LL	11784	20	0,12	175	4,5	X4	4	
M 120/5" A MHC LL	11737	20	0,12	175	4,5	X4	4	
M 120/5" T HCS LL	11702	20	0,12	175	4,5	X4	4	
M 120/5" AT HCS LL	11722	20	0,12	175	4,5	X4	4	
M 120/5" MHC LL	11727	20	0,12	175	4,5	X4	4	
M 150/6"	11401	30	0,15	335	6	X4	3	44,5
M 150/6" P	11851	30	0,15	335	6	X4	3	
M 150/6" T	11411	30	0,15	335	6	X4	3	
M 150/6" A	11421	30	0,15	335	6	X4	3	
M 150/6" AP	11856	30	0,15	335	6	X4	3	
M 150/6" AT	11431	30	0,15	335	6	X4	3	
M 150/6" LL	11402	30	0,15	335	6	X4	3	
M 150/6" T LL	11412	30	0,15	335	6	X4	3	
M 150/6" A LL	11422	30	0,15	335	6	X4	3	
M 150/6" AT LL	11432	30	0,15	335	6	X4	3	
M 150/6" PIR LL	11882	30	0,15	335	6	X4	3	
M 150/6" A PIR LL	11884	30	0,15	335	6	X4	3	
M 150/6" A MHC LL	11837	30	0,15	335	6	X4	3	
M 150/6" T HCS LL	11802	30	0,15	335	6	X4	3	
M 150/6" AT HCS LL	11809	30	0,15	335	6	X4	3	
M 150/6" MHC LL	11827	30	0,15	335	6	X4	3	

220...240 В, Гц В моделях с индексом LL (LONG LIFE) бронзовые шарикоподшипники со сроком службы 30 000 часов